

Packing Instruction 965

Passenger and cargo aircraft for UN 3480

1. Introduction

This entry applies to lithium ion or lithium polymer batteries. This packing instruction is structured as follows:

- Section IA applies to lithium ion cells with a Watt-hour rating in excess of 20 Wh and lithium ion batteries with a Watt-hour rating in excess of 100 Wh, which must be assigned to Class 9 and are subject to all of the applicable requirements of these Instructions;
- Section IB applies to lithium ion cells with a Watt-hour rating not exceeding 20 Wh and lithium ion batteries with a Watt-hour rating not exceeding 100 Wh packed in quantities that exceed the allowance permitted in Section II, Table 965-II; and
- Section II applies to lithium ion cells with a Watt-hour rating not exceeding 20 Wh and lithium ion batteries with a Watt-hour rating not exceeding 100 Wh packed in quantities not exceeding the allowance permitted in Section II, Table 965-II.

2. Lithium batteries forbidden from transport

The following applies to all lithium ion cells and batteries in this packing instruction:

Cells and batteries, identified by the manufacturer as being defective for safety reasons, or that have been damaged, that have the potential of producing a dangerous evolution of heat, fire or short circuit are forbidden for transport (e.g. those being returned to the manufacturer for safety reasons).

Waste lithium batteries and lithium batteries being shipped for recycling or disposal are forbidden from air transport unless approved by the appropriate national authority of the State of Origin and the State of the Operator.

IA. SECTION IA

Each cell or battery must meet all the provisions of 2;9.3.

1A.1 General requirements

Part 4;1 requirements must be met.

Table 965-IA

<i>UN number and proper shipping name</i>	<i>Net quantity per package</i>	
	<i>Passenger</i>	<i>Cargo</i>
UN 3480 Lithium ion batteries	5 kg	35 kg

v # v

Packing Instruction 965

IA.2 Additional requirements

- Lithium ion cells and batteries must be protected against short circuits.
- Lithium ion cells and batteries must be placed in inner packagings that completely enclose the cell or battery then placed in an outer packaging. The completed package for the cells or batteries must meet the Packing Group II performance requirements.
- Lithium ion batteries with a mass of 12 kg or greater and having a strong, impact-resistant outer casing, or assemblies of such batteries, may be transported when packed in strong outer packagings or protective enclosures (e.g. in fully enclosed or wooden slatted crates) not subject to the requirements of Part 6 of these Instructions, if approved by the appropriate authority of the State of Origin. A copy of the document of approval must accompany the consignment.
- Batteries manufactured after 31 December 2011 must be marked with the Watt-hour rating on the outside case.

IA.3 Outer packagings

Boxes

Aluminium (4B)
 Fibreboard (4G)
 Natural wood (4C1, 4C2)
 Other metal (4N)
 Plastics (4H1, 4H2)
 Plywood (4D)
 Reconstituted wood (4F)
 Steel (4A)

Drums

Aluminium (1B2)
 Fibre (1G)
 Other metal (1N2)
 Plastics (1H2)
 Plywood (1D)
 Steel (1A2)

Jerricans

Aluminium (3B2)
 Plastics (3H2)
 Steel (3A2)

IB. SECTION IB

Quantities of lithium ion cells or batteries that exceed the allowance permitted in Section II, Table 965-II are subject to all of the applicable provisions of these Instructions (including the requirements in paragraph 2 of this packing instruction and of this section) except for the the provisions of Part 6.

Lithium ion cells or batteries shipped in accordance with the provisions of Section IB must be described on a dangerous goods transport document as set in Part 5;4. The packing instruction number "965" required by 5;4.1.5.8.1 a) must be supplemented with "IB". All other applicable provisions of Part 5;4 apply.

Lithium ion cells and batteries may be offered for transport provided that each cell and battery meets the provisions of 2;9.3.1 a) and e) and the following:

- 1) for lithium ion cells, the Watt-hour rating (see the Glossary of Terms in Attachment 2) is not more than 20 Wh;
- 2) for lithium ion batteries, the Watt-hour rating is not more than 100 Wh;
 - the Watt-hour rating must be marked on the outside of the battery case except for those batteries manufactured before 1 January 2009;

IB.1 General requirements

Cells and batteries must be packed in strong outer packagings that conform to Part 4;1.1.1, 1.1.3.1 and 1.1.10 (except 1.1.10.1).

Table 965-IB

<i>Contents</i>	<i>Net quantity per package</i>	
	<i>Passenger</i>	<i>Cargo</i>
Lithium ion cells and batteries	10 kg	10 kg

Packing Instruction 965

IB.2 Additional requirements

- Cells and batteries must be packed in inner packagings that completely enclose the cell or battery then placed in a strong outer packaging.
- Cells and batteries must be protected so as to prevent short circuits. This includes protection against contact with conductive materials within the same packaging that could lead to a short circuit.
- Each package must be capable of withstanding a 1.2 m drop test in any orientation without:
 - damage to cells or batteries contained therein;
 - shifting of the contents so as to allow battery to battery (or cell to cell) contact;
 - release of contents.
- Each package must be labelled with a lithium battery handling label (Figure 5-32) in addition to the Class 9 hazard label.
- Each consignment must be accompanied with a document with an indication that:
 - the package contains lithium ion cells or batteries;
 - the package must be handled with care and that a flammability hazard exists if the package is damaged;
 - special procedures must be followed in the event the package is damaged, to include inspection and repacking if necessary; and
 - a telephone number for additional information.

Note.— This information may be provided on the dangerous goods transport document.

IB.3 Outer packagings

Boxes

Drums

Jerricans

Strong outer packagings

II. SECTION II

With the exception of Part 1;2.3 (General — Transport of dangerous goods by post), 7;4.4 (Operator's responsibilities — Reporting of dangerous goods accidents and incidents), 8;1.1 (Provisions concerning passengers and crew — Dangerous goods carried by passengers or crew) and paragraph 2 of this packing instruction, lithium ion cells and batteries offered for transport are not subject to other additional requirements of these Instructions if they meet the requirements of this section.

≠ Lithium ion cells and batteries may be offered for transport provided that each cell and battery meets the provisions of 2;9.3.1 a) and e) and the following:

- 1) for lithium ion cells, the Watt-hour rating (see the Glossary of Terms in Attachment 2) is not more than 20 Wh;
- 2) for lithium ion batteries, the Watt-hour rating is not more than 100 Wh;
 - the Watt-hour rating must be marked on the outside of the battery case except for those batteries manufactured before 1 January 2009.

>

Packing Instruction 965

II.1 General requirements

Cells and batteries must be packed in strong outer packagings that conform to Part 4;1.1.1, 1.1.3.1 and 1.1.10 (except 1.1.10.1).

Table 965-II

<i>Contents</i>	<i>Lithium ion cells and/or batteries with a Watt-hour rating not more than 2.7 Wh</i>	<i>Lithium ion cells with a Watt-hour rating more than 2.7 Wh, but not more than 20 Wh</i>	<i>Lithium ion batteries with a Watt-hour rating more than 2.7 Wh, but not more than 100 Wh</i>
1	2	3	4
Maximum number of cells / batteries per package	No limit	8 cells	2 batteries
Maximum net quantity (mass) per package	2.5 kg	n/a	n/a

The limits specified in columns 2, 3 and 4 of Table 965-II must not be combined in the same package.

II.2 Additional requirements

- Cells and batteries must be packed in inner packagings that completely enclose the cell or battery then placed in a strong outer packaging.
- Cells and batteries must be protected so as to prevent short circuits. This includes protection against contact with conductive materials within the same packaging that could lead to a short circuit.
- Each package must be capable of withstanding a 1.2 m drop test in any orientation without:
 - damage to cells or batteries contained therein;
 - shifting of the contents so as to allow battery to battery (or cell to cell) contact;
 - release of contents.
- Each package must be labelled with a lithium battery handling label (Figure 5-32).
- Each consignment must be accompanied with a document with an indication that:
 - the package contains lithium ion cells or batteries;
 - the package must be handled with care and that a flammability hazard exists if the package is damaged;
 - special procedures must be followed in the event the package is damaged, to include inspection and repacking if necessary; and
 - a telephone number for additional information.
- The words "lithium ion batteries, in compliance with Section II of PI965" must be placed on the air waybill, when an air waybill is used.
- Any person preparing or offering cells or batteries for transport must receive adequate instruction on these requirements commensurate with their responsibilities.

II.3 Outer packagings

Boxes

Drums

Jerricans

Strong outer packagings

II.4 Overpacks

When packages are placed in an overpack, the lithium battery handling label required by this packing instruction must either be clearly visible or the label must be affixed on the outside of the overpack and the overpack must be marked with the word "Overpack".

Packing Instruction 966

Passenger and cargo aircraft for UN 3481 (packed with equipment) only

1. Introduction

This entry applies to lithium ion or lithium polymer batteries packed with equipment.

Section I of this packing instruction applies to lithium ion and lithium polymer cells and batteries that are assigned to Class 9. Certain lithium ion and lithium polymer cells and batteries offered for transport and meeting the requirements of Section II of this packing instruction, subject to paragraph 2 below, are not subject to other additional requirements of these Instructions.

2. Lithium batteries forbidden from transport

The following applies to all lithium ion cells and batteries in this packing instruction:

Cells and batteries, identified by the manufacturer as being defective for safety reasons, or that have been damaged, that have the potential of producing a dangerous evolution of heat, fire or short circuit are forbidden for transport (e.g. those being returned to the manufacturer for safety reasons).

I. SECTION I

Each cell or battery must meet all the provisions of 2;9.3.

I.1 General requirements

Part 4;1 requirements must be met.

<i>UN number and proper shipping name</i>	<i>Package quantity (Section I)</i>	
	<i>Passenger</i>	<i>Cargo</i>
UN 3481 Lithium ion batteries packed with equipment	5 kg of lithium ion cells or batteries	35 kg of lithium ion cells or batteries

>
≠
>

Packing Instruction 966

I.2 Additional requirements

- Lithium ion cells and batteries must be protected against short circuits.
- Lithium ion cells or batteries must:
 - be placed in inner packagings that completely enclose the cell or battery then placed in an outer packaging. The completed package for the cells or batteries must meet the Packing Group II performance requirements; or
 - be placed in inner packagings that completely enclose the cell or battery, then placed with equipment in a packaging that meets the Packing Group II performance requirements.
- The equipment must be secured against movement within the outer packaging and must be equipped with an effective means of preventing accidental activation.
- The number of cells or batteries in each package must not exceed the appropriate number for the equipment's operation, plus two spares.
- For the purpose of this packing instruction, "equipment" means apparatus requiring the lithium ion batteries with which it is packed for its operation.
- Batteries manufactured after 31 December 2011 must be marked with the Watt-hour rating on the outside case.

I.3 Outer packagings

Boxes

- Aluminium (4B)
- Fibreboard (4G)
- Natural wood (4C1, 4C2)
- Other metal (4N)
- Plastics (4H1, 4H2)
- Plywood (4D)
- Reconstituted wood (4F)
- Steel (4A)

Drums

- Aluminium (1B2)
- Fibre (1G)
- Other metal (1N2)
- Plastics (1H2)
- Plywood (1D)
- Steel (1A2)

Jerricans

- Aluminium (3B2)
- Plastics (3H2)
- Steel (3A2)

II. SECTION II

With the exception of Part 1;2.3 (Transport of dangerous goods by post), 7;4.4 (Reporting of dangerous goods accidents and incidents), 8;1.1 (Dangerous goods carried by passengers or crew) and paragraph 2 of this packing instruction, lithium ion cells and batteries packed with equipment offered for transport are not subject to other additional requirements of these Instructions if they meet the requirements of this section.

Lithium ion cells and batteries may be offered for transport provided that each cell and battery meets the provisions of 2;9.3.1 a) and e) and the following:

- 1) for lithium ion cells, the Watt-hour rating (see the Glossary of Terms in Attachment 2) is not more than 20 Wh;
- 2) for lithium ion batteries, the Watt-hour rating is not more than 100 Wh;
 - the Watt-hour rating must be marked on the outside of the battery case except for those batteries manufactured before 1 January 2009.

II.1 General requirements

Cells and batteries must be packed in strong outer packagings that conform to Part 4;1.1.1, 1.1.3.1 and 1.1.10 (except 1.1.10.1).

<i>Contents</i>	<i>Package quantity (Section II)</i>	
	<i>Passenger</i>	<i>Cargo</i>
Net quantity of lithium ion cells or batteries per package	5 kg	5 kg

Packing Instruction 966

II.2 Additional requirements

- Lithium ion cells and batteries must:
 - be placed in inner packagings that completely enclose the cell or battery, then placed in a strong outer packaging; or
 - be placed in inner packagings that completely enclose the cell or battery, then placed with the equipment in a strong outer packaging.
- Cells and batteries must be protected so as to prevent short circuits. This includes protection against contact with conductive materials within the same packaging that could lead to a short circuit.
- The equipment must be secured against movement within the outer packaging and must be equipped with an effective means of preventing accidental activation.
- The number of cells or batteries in each package must not exceed the appropriate number for the equipment's operation, plus two spares.
- Each package of cells or batteries, or the completed package, must be capable of withstanding a 1.2 m drop test in any orientation without:
 - damage to cells or batteries contained therein;
 - shifting of the contents so as to allow battery to battery (or cell to cell) contact;
 - release of contents.
- Each package must be labelled with a lithium battery handling label (Figure 5-32).
- Each consignment must be accompanied with a document with an indication that:
 - the package contains lithium ion cells or batteries;
 - the package must be handled with care and that a flammability hazard exists if the package is damaged;
 - special procedures must be followed in the event the package is damaged, to include inspection and repacking if necessary; and
 - a telephone number for additional information.
- The words "lithium ion batteries, in compliance with Section II of PI966" must be placed on the air waybill, when an air waybill is used.
- Any person preparing or offering cells or batteries for transport must receive adequate instruction on these requirements commensurate with their responsibilities.

II.3 Outer packagings

Boxes

Drums

Jerricans

Strong outer packagings

II.4 Overpacks

When packages are placed in an overpack, the lithium battery handling label required by this packing instruction must either be clearly visible or the label must be affixed on the outside of the overpack and the overpack must be marked with the word "Overpack".

Packing Instruction 967

Passenger and cargo aircraft for UN 3481 (contained in equipment) only

1. Introduction

This entry applies to lithium ion or lithium polymer batteries contained in equipment.

Section I of this packing instruction applies to lithium ion and lithium polymer cells and batteries that are assigned to Class 9. Certain lithium ion and lithium polymer cells and batteries offered for transport and meeting the requirements of Section II of this packing instruction, subject to paragraph 2 below, are not subject to other additional requirements of these Instructions.

2. Lithium batteries forbidden from transport

The following applies to all lithium ion cells and batteries in this packing instruction:

Cells and batteries, identified by the manufacturer as being defective for safety reasons, or that have been damaged, that have the potential of producing a dangerous evolution of heat, fire or short circuit are forbidden for transport (e.g. those being returned to the manufacturer for safety reasons).

Packing Instruction 967

I. SECTION I

Each cell or battery must meet all the provisions of 2;9.3.

I.1 General requirements

Equipment must be packed in strong outer packagings that conform to Part 4;1.1.1, 1.1.3.1 and 1.1.10 (except 1.1.10.1).

<i>UN number and proper shipping name</i>	<i>Package quantity (Section I)</i>	
	<i>Passenger</i>	<i>Cargo</i>
UN 3481 Lithium ion batteries contained in equipment	5 kg of lithium ion cells or batteries	35 kg of lithium ion cells or batteries

I.2 Additional requirements

- The equipment must be secured against movement within the outer packaging and be packed so as to prevent accidental operation during air transport.
- The equipment must be packed in strong outer packagings constructed of suitable material of adequate strength and design in relation to the packaging's capacity and its intended use unless the battery is afforded equivalent protection by the equipment in which it is contained.
- Batteries manufactured after 31 December 2011 must be marked with the Watt-hour rating on the outside case.

I.3 Outer packagings

Boxes

Drums

Jerricans

Strong outer packagings

II. SECTION II

With the exception of Part 1;2.3 (Transport of dangerous goods by post), 7;4.4 (Reporting of dangerous goods accidents and incidents), 8;1.1 (Dangerous goods carried by passengers or crew) and paragraph 2 of this packing instruction, lithium ion cells and batteries contained in equipment offered for transport are not subject to other additional requirements of these Instructions if they meet the requirements of this section.

Lithium ion cells and batteries may be offered for transport provided that each cell and battery meets the provisions of 2;9.3.1 a) and e) and the following:

- 1) for lithium ion cells, the Watt-hour rating (see the Glossary of Terms in Attachment 2) is not more than 20 Wh;
- 2) for lithium ion batteries, the Watt-hour rating is not more than 100 Wh;
 - the Watt-hour rating must be marked on the outside of the battery case except for those batteries manufactured before 1 January 2009.

Packing Instruction 967

Devices such as radio frequency identification (RFID) tags, watches and temperature loggers, which are not capable of generating a dangerous evolution of heat, may be transported when intentionally active. When active, these devices must meet defined standards for electromagnetic radiation to ensure that the operation of the device does not interfere with aircraft systems. The devices must not be capable of emitting disturbing signals (such as buzzing alarms, strobe lights, etc.) during transport.

II.1 General requirements

Equipment must be packed in strong outer packagings that conform to Part 4;1.1.1, 1.1.3.1 and 1.1.10 (except 1.1.10.1).

<i>Contents</i>	<i>Package quantity (Section II)</i>	
	<i>Passenger</i>	<i>Cargo</i>
Net quantity of lithium ion cells or batteries per package	5 kg	5 kg

II.2 Additional requirements

- The equipment must be secured against movement within the outer packaging and must be equipped with an effective means of preventing accidental activation.
- Cells and batteries must be protected so as to prevent short circuits.
- The equipment must be packed in strong outer packagings constructed of suitable material of adequate strength and design in relation to the packaging's capacity and its intended use unless the battery is afforded equivalent protection by the equipment in which it is contained.
- Each package containing more than four cells or more than two batteries installed in equipment must be labelled with a lithium battery handling label (Figure 5-32) (except button cell batteries installed in equipment (including circuit boards)).
- Each consignment with packages bearing the lithium battery handling label must be accompanied with a document with an indication that:
 - the package contains lithium ion cells or batteries;
 - the package must be handled with care and that a flammability hazard exists if the package is damaged;
 - special procedures must be followed in the event the package is damaged, to include inspection and repacking if necessary; and
 - a telephone number for additional information.
- Where a consignment includes packages bearing the lithium battery handling label, the words "lithium ion batteries, in compliance with Section II of PI967" must be placed on the air waybill, when an air waybill is used.
- Any person preparing or offering cells or batteries for transport must receive adequate instruction on these requirements commensurate with their responsibilities.

II.3 Outer packagings

Boxes

Drums

Jerricans

Strong outer packagings

II.4 Overpacks

When packages are placed in an overpack, the lithium battery handling label required by this packing instruction must either be clearly visible or the label must be affixed on the outside of the overpack and the overpack must be marked with the word "Overpack".

#

Packing Instruction 968

Cargo aircraft only for UN 3090

1. Introduction

This entry applies to lithium metal or lithium alloy batteries. This packing instruction is structured as follows:

- Section IA applies to lithium metal cells with a lithium metal content in excess of 1 g and lithium metal batteries with a lithium metal content in excess of 2 g, which must be assigned to Class 9 and are subject to all of the applicable requirements of these Instructions;
- Section IB applies to lithium metal cells with a lithium metal content not exceeding 1 g and lithium metal batteries with a lithium metal content not exceeding 2 g packed in quantities that exceed the allowance permitted in Section II, Table 968-II; and
- Section II applies to lithium metal cells with a lithium metal content not exceeding 1 g and lithium metal batteries with a lithium metal content not exceeding 2 g packed in quantities not exceeding the allowance permitted in Section II, Table 968-II.

2. Lithium batteries forbidden from transport

The following applies to all lithium metal cells and batteries in this packing instruction:

Cells and batteries, identified by the manufacturer as being defective for safety reasons, or that have been damaged, that have the potential of producing a dangerous evolution of heat, fire or short circuit are forbidden for transport (e.g. those being returned to the manufacturer for safety reasons).

Waste lithium batteries and lithium batteries being shipped for recycling or disposal are forbidden from air transport unless approved by the appropriate national authority of the State of Origin and the State of the Operator.

IA. SECTION IA

Each cell or battery must meet all the provisions of 2;9.3.

IA.1 General requirements

Part 4;1 requirements must be met.

Table 968-IA

<i>UN number and proper shipping name</i>	<i>Net quantity per package</i>	
	<i>Passenger</i>	<i>Cargo</i>
UN 3090 Lithium metal batteries	Forbidden	35 kg

#

∨ # ∨

Packing Instruction 968

IA.2 Additional requirements

- Lithium metal cells and batteries must be protected against short circuits.
- Lithium metal cells and batteries must be placed in inner packagings that completely enclose the cell or battery, then placed in an outer packaging. The completed package for the cells or batteries must meet the Packing Group II performance requirements.
- Lithium metal batteries with a mass of 12 kg or greater and having a strong, impact-resistant outer casing, or assemblies of such batteries, may be transported when packed in strong outer packagings or protective enclosures (e.g. in fully enclosed or wooden slatted crates) not subject to the requirements of Part 6 of these Instructions, if approved by the appropriate authority of the State of Origin. A copy of the document of approval must accompany the consignment.

IA.3 Outer packagings

<i>Boxes</i>	<i>Drums</i>	<i>Jerricans</i>
Aluminium (4B)	Aluminium (1B2)	Aluminium (3B2)
Fibreboard (4G)	Fibre (1G)	Plastics (3H2)
Natural wood (4C1, 4C2)	Other metal (1N2)	Steel (3A2)
Other metal (4N)	Plastics (1H2)	
Plastics (4H1, 4H2)	Plywood (1D)	
Plywood (4D)	Steel (1A2)	
Reconstituted wood (4F)		
Steel (4A)		

IB. SECTION IB

Quantities of lithium metal cells or batteries that exceed the allowance permitted in Section II, Table 968-II, are subject to all of the applicable provisions of these Instructions (including the requirements in paragraph 2 of this packing instruction and of this section) except for the provisions of Part 6.

Lithium metal cells or batteries shipped in accordance with the provisions of Section IB must be described on a dangerous goods transport document as set in Part 5;4. The packing instruction number "968" required by 5;4.1.5.8.1 a) must be supplemented with "IB". All other applicable provisions of Part 5;4 apply.

Lithium metal or lithium alloy cells and batteries may be offered for transport provided that each cell and battery meets the provisions of 2;9.3.1 a) and e) and the following:

- 1) for lithium metal cells, the lithium content is not more than 1 g;
- 2) for lithium metal or lithium alloy batteries, the aggregate lithium content is not more than 2 g.

Packing Instruction 968

IB.1 General requirements

Cells and batteries must be packed in strong outer packagings that conform to Part 4;1.1.1, 1.1.3.1 and 1.1.10 (except 1.1.10.1).

Table 968-IB

≠ ≠	Contents	Net quantity per package	
		Passenger	Cargo
	Lithium metal cells and batteries	Forbidden	2.5 kg

IB.2 Additional requirements

- Cells and batteries must be packed in inner packagings that completely enclose the cell or battery then placed in a strong outer packaging.
- Cells and batteries must be protected so as to prevent short circuits. This includes protection against contact with conductive materials within the same packaging that could lead to a short circuit.
- Each package must be capable of withstanding a 1.2 m drop test in any orientation without:
 - damage to cells or batteries contained therein;
 - shifting of the contents so as to allow battery to battery (or cell to cell) contact;
 - release of contents.
- Each package must be labelled with a lithium battery handling label (Figure 5-32) in addition to the Class 9 hazard label and the cargo aircraft only label (Figure 5-26).
- Each consignment must be accompanied with a document with an indication that:
 - the package contains lithium metal cells or batteries;
 - the package must be handled with care and that a flammability hazard exists if the package is damaged;
 - special procedures must be followed in the event the package is damaged, to include inspection and repacking if necessary; and
 - a telephone number for additional information.

Note.— This information may be provided on the dangerous goods transport document.

IB.3 Outer packagings

Boxes

Drums

Jerricans

Strong outer packagings

II. SECTION II

With the exception of Part 1;2.3 (General — Transport of dangerous goods by post), 5;1.1 g), 5;1.1 j) (Shipper's responsibilities — General requirements), 7;2.1 (Operator's responsibilities — Loading restrictions on the flight deck and for passenger aircraft), 7;2.4.1 (Operator's responsibilities — Loading of cargo aircraft), 7;4.4 (Operator's responsibilities — Reporting of dangerous goods accidents and incidents), 8;1.1 (Provisions concerning passengers and crew — Dangerous goods carried by passengers or crew) and paragraph 2 of this packing instruction, lithium metal or lithium alloy cells and batteries offered for transport are not subject to other additional requirements of these Instructions if they meet the requirements of this section.

Lithium metal or lithium alloy cells and batteries may be offered for transport provided that each cell and battery meets the provisions of 2;9.3.1 a) and e) and the following:

- 1) for a lithium metal cell, the lithium content is not more than 1 g;
- 2) for a lithium metal or lithium alloy battery, the aggregate lithium content is not more than 2 g.

II.1 General requirements

Cells and batteries must be packed in strong outer packagings that conform to Part 4;1.1.1, 1.1.3.1 and 1.1.10 (except 1.1.10.1).

Packing Instruction 968

Table 968-II

<i>Contents</i>	<i>Lithium metal cells and/or batteries with a lithium content not more than 0.3 g</i>	<i>Lithium metal cells with a lithium content more than 0.3 g but not more than 1 g</i>	<i>Lithium metal batteries with a lithium content more than 0.3 g but not more than 2 g</i>
1	2	3	4
Maximum number of cells / batteries per package	No limit	8 cells	2 batteries
Maximum net quantity (mass) per package	2.5 kg	n/a	n/a

The limits specified in columns 2, 3 and 4 of Table 968-II must not be combined in the same package.

II.2 Additional requirements

- Cells and batteries must be packed in inner packagings that completely enclose the cell or battery, then placed in a strong outer packaging.
- Cells and batteries must be protected so as to prevent short circuits. This includes protection against contact with conductive materials within the same packaging that could lead to a short circuit.
- Each package must be capable of withstanding a 1.2 m drop test in any orientation without:
 - damage to cells or batteries contained therein;
 - shifting of the contents so as to allow battery to battery (or cell to cell) contact;
 - release of contents.
- Each package must be labelled with a lithium battery handling label (Figure 5-32) and the cargo aircraft only label (Figure 5-26).
 - the cargo aircraft only label must be located on the same surface of the package near the lithium battery handling label, if the package dimensions are adequate.
- Each consignment must be accompanied with a document with an indication that:
 - the package contains lithium metal cells or batteries;
 - the package must be handled with care and that a flammability hazard exists if the package is damaged;
 - special procedures must be followed in the event the package is damaged, to include inspection and repacking if necessary; and
 - a telephone number for additional information.
- The words "lithium metal batteries, in compliance with Section II of PI968 — cargo aircraft only" or "lithium metal batteries, in compliance with Section II of PI968 — CAO" must be placed on the air waybill, when an air waybill is used.
- Consignments of lithium metal batteries prepared in accordance with the provisions of Section II must not be consolidated with other shipments of dangerous goods or non-dangerous goods and must not be loaded into a unit load device before being offered to the operator.
- Any person preparing or offering cells or batteries for transport must receive adequate instruction on these requirements commensurate with their responsibilities.

II.3 Outer packagings

Boxes

Drums

Jerricans

Strong outer packagings

II.4 Overpacks

When packages are placed in an overpack, the lithium battery handling label and the cargo aircraft only label (Figure 5-26) required by this packing instruction must either be clearly visible or the labels must be affixed on the outside of the overpack and the overpack must be marked with the word "Overpack".

Packing Instruction 969

Passenger and cargo aircraft for UN 3091 (packed with equipment) only

1. Introduction

This entry applies to lithium metal or lithium alloy batteries packed with equipment.

Section I of this packing instruction applies to lithium metal and lithium alloy cells and batteries that are assigned to Class 9. Certain lithium metal and lithium alloy cells and batteries offered for transport and meeting the requirements of Section II of this packing instruction, subject to paragraph 2 below, are not subject to other additional requirements of these Instructions.

2. Lithium batteries forbidden from transport

The following applies to all lithium metal cells and batteries in this packing instruction:

Cells and batteries, identified by the manufacturer as being defective for safety reasons, or that have been damaged, that have the potential of producing a dangerous evolution of heat, fire or short circuit are forbidden for transport (e.g. those being returned to the manufacturer for safety reasons).

I. SECTION I

Each cell or battery must meet all the provisions of 2;9.3.

I.1 General requirements

Part 4;1 requirements must be met.

<i>UN number and proper shipping name</i>	<i>Package quantity (Section I)</i>	
	<i>Passenger</i>	<i>Cargo</i>
UN 3091 Lithium metal batteries packed with equipment	5 kg of lithium metal cells or batteries	35 kg of lithium metal cells or batteries

Packing Instruction 969

I.2 Additional requirements

- Lithium metal cells and batteries must be protected against short circuits.
- Lithium metal cells or batteries must:
 - be placed in inner packagings that completely enclose the cell or battery, then placed in an outer packaging. The completed package for the cells or batteries must meet the Packing Group II performance requirements; or
 - be placed in inner packagings that completely enclose the cell or battery, then placed with equipment in a packaging that meets the Packing Group II performance requirements.
- The equipment must be secured against movement within the outer packaging and must be equipped with an effective means of preventing accidental activation.
- The number of cells or batteries in each package must not exceed the appropriate number for the equipment's operation, plus two spares.
- For the purpose of this packing instruction, "equipment" means apparatus requiring the lithium batteries with which it is packed for its operation.
- For lithium metal cells and batteries prepared for transport on passenger aircraft as Class 9:
 - cells and batteries offered for transport on passenger aircraft must be packed in intermediate or outer rigid metal packaging surrounded by cushioning material that is non-combustible and non-conductive and placed inside an outer packaging.

I.3 Outer packagings

<i>Boxes</i>	<i>Drums</i>	<i>Jerricans</i>
Aluminium (4B)	Aluminium (1B2)	Aluminium (3B2)
Fibreboard (4G)	Fibre (1G)	Plastics (3H2)
Natural wood (4C1, 4C2)	Other metal (1N2)	Steel (3A2)
Other metal (4N)	Plastics (1H2)	
Plastics (4H1, 4H2)	Plywood (1D)	
Plywood (4D)	Steel (1A2)	
Reconstituted wood (4F)		
Steel (4A)		

II. SECTION II

With the exception of Part 1;2.3 (Transport of dangerous goods by post), 7;4.4 (Reporting of dangerous goods accidents and incidents);8;1.1 (Dangerous goods carried by passengers or crew) and paragraph 2 of this packing instruction, lithium metal cells and batteries packed with equipment offered for transport are not subject to other additional requirements of these Instructions if they meet the requirements of this section.

Lithium metal cells and batteries may be offered for transport provided that each cell and battery meets the provisions of 2;9.3.1 a) and e) and the following:

- 1) for a lithium metal cell, the lithium content is not more than 1 g;
- 2) for a lithium metal or lithium alloy battery, the aggregate lithium content is not more than 2 g.

II.1 General requirements

Cells and batteries must be packed in strong outer packagings that conform to Part 4;1.1.1, 1.1.3.1 and 1.1.10 (except 1.1.10.1).

<i>Contents</i>	<i>Package quantity (Section II)</i>	
	<i>Passenger</i>	<i>Cargo</i>
Net quantity of lithium metal cells or batteries per package	5 kg	5 kg

Packing Instruction 969

II.2 Additional requirements

- Lithium metal cells or batteries must:
 - be placed in inner packagings that completely enclose the cell or battery, then placed in a strong outer packaging; or
 - be placed in inner packagings that completely enclose the cell or battery, then placed with the equipment in a strong outer packaging.
- Cells and batteries must be protected so as to prevent short circuits. This includes protection against contact with conductive materials within the same packaging that could lead to a short circuit.
- The equipment must be secured against movement within the outer packaging and must be equipped with an effective means of preventing accidental activation.
- The number of cells or batteries in each package must not exceed the appropriate number for the equipment's operation, plus two spares.
- Each package of cells or batteries, or the completed package, must be capable of withstanding a 1.2 m drop test in any orientation without:
 - damage to cells or batteries contained therein;
 - shifting of the contents so as to allow battery to battery (or cell to cell) contact;
 - release of contents.
- Each package must be labelled with a lithium battery handling label (Figure 5-32).
- Each consignment must be accompanied with a document with an indication that:
 - the package contains lithium metal cells or batteries;
 - the package must be handled with care and that a flammability hazard exists if the package is damaged;
 - special procedures must be followed in the event the package is damaged, to include inspection and repacking if necessary; and
 - a telephone number for additional information.
- The words "lithium metal batteries, in compliance with Section II of PI969" must be placed on the air waybill, when an air waybill is used.
- Any person preparing or offering cells or batteries for transport must receive adequate instruction on these requirements commensurate with their responsibilities.

II.3 Outer packagings

Boxes

Drums

Jerricans

Strong outer packagings

II.4 Overpacks

When packages are placed in an overpack, the lithium battery handling label required by this packing instruction must either be clearly visible or the label must be affixed on the outside of the overpack and the overpack must be marked with the word "Overpack".

Packing Instruction 970

Passenger and cargo aircraft for UN 3091 (contained in equipment) only

1. Introduction

This entry applies to lithium metal or lithium alloy batteries contained in equipment.

Section I of this packing instruction applies to lithium metal and lithium alloy cells and batteries that are assigned to Class 9. Certain lithium metal and lithium alloy cells and batteries offered for transport and meeting the requirements of Section II of this packing instruction, subject to paragraph 2 below, are not subject to other additional requirements of these Instructions.

2. Lithium batteries forbidden from transport

The following applies to all lithium metal cells and batteries in this packing instruction:

Cells and batteries, identified by the manufacturer as being defective for safety reasons, or that have been damaged, that have the potential of producing a dangerous evolution of heat, fire or short circuit are forbidden for transport (e.g. those being returned to the manufacturer for safety reasons).

Packing Instruction 970

I. SECTION I

Each cell or battery must meet all the provisions of 2;9.3.

I.1 General requirements

Equipment must be packed in strong outer packagings that conform to Part 4;1.1.1, 1.1.3.1 and 1.1.10 (except 1.1.10.1).

UN number and proper shipping name	Package quantity (Section I)	
	Passenger	Cargo
UN 3091 Lithium metal batteries contained in equipment	5 kg of lithium metal cells or batteries	35 kg of lithium metal cells or batteries

I.2 Additional requirements

- The equipment must be secured against movement within the outer packaging and must be equipped with an effective means of preventing accidental activation.
- The equipment must be packed in strong outer packagings constructed of suitable material of adequate strength and design in relation to the packaging's capacity and its intended use unless the battery is afforded equivalent protection by the equipment in which it is contained.
- The quantity of lithium metal contained in any piece of equipment must not exceed 12 g per cell and 500 g per battery.

I.3 Outer packagings

Boxes

Drums

Jerricans

Strong outer packagings

II. SECTION II

With the exception of Part 1;2.3 (Transport of dangerous goods by post), 7;4.4 (Reporting of dangerous goods accidents and incidents), 8;1.1 (Dangerous goods carried by passengers or crew) and paragraph 2 of this packing instruction, lithium metal cells and batteries contained in equipment offered for transport are not subject to other additional requirements of these Instructions if they meet the requirements of this section.

Lithium metal cells and batteries may be offered for transport provided that each cell and battery meets the provisions of 2;9.3.1 a) and e) and the following:

- 1) for a lithium metal cell, the lithium content is not more than 1 g;
- 2) for a lithium metal or lithium alloy battery, the aggregate lithium content is not more than 2 g.

Devices such as radio frequency identification (RFID) tags, watches and temperature loggers, which are not capable of generating a dangerous evolution of heat, may be transported when intentionally active. When active, these devices must meet defined standards for electromagnetic radiation to ensure that the operation of the device does not interfere with aircraft systems. The devices must not be capable of emitting disturbing signals (such as buzzing alarms, strobe lights, etc.) during transport.

II.1 General requirements

Equipment containing batteries must be packed in strong outer packagings that conform to Part 4;1.1.1, 1.1.3.1 and 1.1.10 (except 1.1.10.1).

Contents	Package quantity (Section II)	
	Passenger	Cargo
Net quantity of lithium metal cells or batteries per package	5 kg	5 kg

II.2 Additional requirements

- The equipment must be secured against movement within the outer packaging and must be equipped with an effective means of preventing accidental activation.
- Cells and batteries must be protected so as to prevent short circuits.
- The equipment must be packed in strong outer packagings constructed of suitable material of adequate strength and design in relation to the packaging's capacity and its intended use unless the battery is afforded equivalent protection by the equipment in which it is contained.
- Each package containing more than four cells or more than two batteries installed in equipment must be labelled with a lithium battery handling label (Figure 5-32) (except button cell batteries installed in equipment (including circuit boards)).
- Each consignment with packages bearing the lithium battery handling label must be accompanied with a document with an indication that:
 - the package contains lithium metal cells or batteries;
 - the package must be handled with care and that a flammability hazard exists if the package is damaged;
 - special procedures must be followed in the event the package is damaged, to include inspection and repacking if necessary; and
 - a telephone number for additional information.
- Where a consignment includes packages bearing the lithium battery handling label, the words "lithium ion batteries, in compliance with Section II of PI970" must be placed on the air waybill, when an air waybill is used.
- Any person preparing or offering cells or batteries for transport must receive adequate instruction on these requirements commensurate with their responsibilities.

II.3 Outer packagings

Boxes

Drums

Jerricans

Strong outer packagings

II.4 Overpacks

When packages are placed in an overpack, the lithium battery handling label required by this packing instruction must either be clearly visible or the label must be affixed on the outside of the overpack and the overpack must be marked with the word "Overpack".